

## Declaration of Performance

2 layer Style68 Meranti/Alu



The performance of the product is in conformity with the declared performance.  
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset  
Identification: 2 layer Style68 Meranti/Alu  
Intended use: Dedicated for use in residential and public buildings  
Manufacturer: JABS Group A/S, Kratholmvej 27B  
DK,5260 Odense S, Denmark  
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016  
Windows and doors - Product standard,  
Performance characteristics -  
Part 1: windows and external pedestrian doorset

### Declared performance:

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	1,36
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen  
Managing Director

Odense, 2023-05-23



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

23

DoP ref. St682023-MA2

EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Style68 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,36
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

## Declaration of Performance

2 layer Thermo80 Meranti/Alu



The performance of the product is in conformity with the declared performance.  
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset  
Identification: 2 layer Thermo80 Meranti/Alu  
Intended use: Dedicated for use in residential and public buildings  
Manufacturer: JABS Group A/S, Kratholmvej 27B  
DK,5260 Odense S, Denmark  
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3  
Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016  
Windows and doors - Product standard,  
Performance characteristics -  
Part 1: windows and external pedestrian doorset

Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	1,28
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen  
Managing Director

Odense, 2023-05-23



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

23

DoP ref. Th802023-MA2  
EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Thermo80 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,28
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

## Declaration of Performance

3 layer Thermo80 Meranti/Alu



The performance of the product is in conformity with the declared performance.  
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset  
Identification: 3 layer Thermo80 Meranti/Alu  
Intended use: Dedicated for use in residential and public buildings  
Manufacturer: JABS Group A/S, Kratholmvej 27B  
DK,5260 Odense S, Denmark  
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3  
Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016  
Windows and doors - Product standard,  
Performance characteristics -  
Part 1: windows and external pedestrian doorset

Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	0,94
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen  
Managing Director

Odense, 2023-05-23



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

23

DoP ref. Th802023-MA3  
EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Thermo80 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,94
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

## Declaration of Performance

3 layer Elite92 Meranti/Alu



The performance of the product is in conformity with the declared performance.  
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset  
Identification: 3 layer Elite92 Meranti/Alu  
Intended use: Dedicated for use in residential and public buildings  
Manufacturer: JABS Group A/S, Kratholmvej 27B  
DK,5260 Odense S, Denmark  
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3  
Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016  
Windows and doors - Product standard,  
Performance characteristics -  
Part 1: windows and external pedestrian doorset

Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen  
Managing Director

Odense, 2023-05-23



JABS Group A/S  
Kratholmvej 27B  
DK,5260 Odense S  
Denmark

23

DoP ref. EI922023-MA3

EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Elite92 Meranti/Alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523  
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.