

Declaration of Performance

2 layer Style68 Meranti



The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 2 layer Style68 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3
Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	1,36
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. St682023-M2

EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Style68 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,36
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

2 layer Thermo80 Meranti



The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 2 layer Thermo80 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3
Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance:	
Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	1,28
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. Th802023-M2

EN 14351-1:2006 + A2:2016

Windows - Type: 2 layer Thermo80 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,28
Radiation properties:	
- Solar factor (gg-value):	0,63
- Light transmittance (LTg-value):	0,80
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Thermo80 Meranti



The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Thermo80 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance:

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	0,94
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. Th802023-M3

EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Thermo80 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,94
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.

Declaration of Performance

3 layer Elite92 Meranti



The performance of the product is in conformity with the declared performance.
The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset
Identification: 3 layer Elite92 Meranti
Intended use: Dedicated for use in residential and public buildings
Manufacturer: JABS Group A/S, Kratholmvej 27B
DK,5260 Odense S, Denmark
phone +45 70231523, e-mail info@jabsgroup.com

The Assessment and Verification of Constancy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Declared performance:

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 230x1480 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2023-05-23



JABS Group A/S
Kratholmvej 27B
DK,5260 Odense S
Denmark

23

DoP ref. EI922023-M3

EN 14351-1:2006 + A2:2016

Windows - Type: 3 layer Elite92 Meranti

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	0,84
Radiation properties:	
- Solar factor (gg-value):	0,50
- Light transmittance (LTg-value):	0,71
Air permeability:	npd

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70231523
acc. EN 14351-1:2006+A2:2016, Table E.1 note c.