



Declaration of performance

ESD/DOP-Nr.267

1. Product system	PVC Euro70 I TATRO
2. Application	Inward opening windows, fixed frame windows and balcony doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Turn/Tilt window	Kipp window	Fixed frame window	Combination window °c	Single sash Turn/Tilt balcony door	Double sash Turn/Tilt balcony double sash door
Product ID	PK	KF	PF	PK-FR	TK	DK
Product measurements	1230x1480	1230x1480	1230x1480	2000x1480	1230x2180	2000x2180
Air permeability (EN 12207)	4	4	4	4	4	4
Water tightness (EN 12208)	9A	9A	9A	9A	9A	9A
Wind resistance (EN 12210)	B5	B5	B5	B2	B5	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*1,3	*1,3	*1,2	*1,3	*1,2	*1,3
Light transmission T_L , % (EN 410)	*82	*82	*82	*82	*82	*82
Solar energy transmission g , % (EN 410)	*65	*65	*65	*65	*65	*65
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)

* formula of glass panel (4-16ar (SWS)-4 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is clear glass. Warm edge is included in gap - Swisspacer (advanced), gap is filled with argon gas – 90%;

^{*a} formula of glass panel (44.2 SS-16ar-10 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

^{*b} formula of glass panel (66.2 SS-16ar-8 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

^{°c} Double sash escape window. Slave sash with movable mullion;

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895



Declaration of performance

ESD/DOP-Nr.268

1. Product system	PVC Euro70 I TATRO
2. Application	Inward opening windows, fixed frame windows and balcony doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Turn/Tilt window	Kipp window	Fixed frame window	Combination window °c	Single sash Turn/Tilt balcony door	Double sash Turn/Tilt balcony double sash door
Product ID	PK	KF	PF	PK-FR	TK	DK
Product measurements	1230x1480	1230x1480	1230x1480	2000x1480	1230x2180	2000x2180
Air permeability (EN 12207)	4	4	4	4	4	4
Water tightness (EN 12208)	9A	9A	9A	9A	9A	9A
Wind resistance (EN 12210)	B5	B5	B5	B2	B5	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*0,90	*0,90	*0,82	*0,91	*0,88	*0,86
Light transmission T_L , % (EN 410)	*73	*73	*73	*73	*73	*73
Solar energy transmission g , % (EN 410)	*53	*53	*53	*53	*53	*53
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)	^{*a} 44 (-1;-3) ^{*b} 45 (-1;-2)

* formula of glass panel (4XN-14ar (SWS)-4-14ar (SWS)-4 XN) – 3 layers of glass. Inner and outer glass with selective coating, middle glass is clear glass. Warm edge is included in gaps - Swisspacer (advanced), gaps are filled with argon gas – 90%;

^{*a} formula of glass panel (44.2 SS-16ar-10 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

^{*b} formula of glass panel (66.2 SS-16ar-8 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

^{°c} Double sash escape window. Slave sash with movable mullion;

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895



Declaration of performance

ESD/DOP-Nr.263

1. Product system	PVC Euro70 I TATRO
2. Application	Entrance-doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Single sash Entrance door (20mm ALU threshold)**	Double sash Entrance door (20mm ALU threshold)**	Single sash Entrance door (20mm ALU threshold)***	Double sash Entrance door (20mm ALU threshold)***
Product ID	EFD	EDF	EFD	EDF
Product measurements	1230x2180	2000x2180	1230x2180	2000x2180
Air permeability (EN 12207)	3	3	4	4
Water tightness (EN 12208)	4A	4A	5B	5B
Wind resistance (EN 12210)	B2	B2	B2	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*1.4	*1.4	*1.4	*1.4
Light transmission T_L , % (EN 410)	*82	*82	*82	*82
Solar energy transmission g , % (EN 410)	*65	*65	*65	*65
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	-	-	-	-

* formula of glass panel (4-16ar (SWS)-4 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is clear glass. Warm edge is included in gap - Swisspacer (advanced), gap is filled with argon gas – 90%.

** Doors opens to inside;

*** Doors opens to outside;

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895



Declaration of performance

ESD/DOP-Nr.264

1. Product system	PVC Euro70 I TATRO
2. Application	Entrance-doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Single sash Entrance door (20mm ALU threshold)**	Double sash Entrance door (20mm ALU threshold)**	Single sash Entrance door (20mm ALU threshold)***	Double sash Entrance door (20mm ALU threshold)***
Product ID	EFD	EDF	EFD	EDF
Product measurements	1230x2180	2000x2180	1230x2180	2000x2180
Air permeability (EN 12207)	3	3	4	4
Water tightness (EN 12208)	4A	4A	5B	5B
Wind resistance (EN 12210)	B2	B2	B2	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*1.1	*1.1	*1.1	*1.1
Light transmission T_L , % (EN 410)	*73	*73	*73	*73
Solar energy transmission g , % (EN 410)	*53	*53	*53	*53
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	-	-	-	-

* formula of glass panel (4XN-14ar (SWS)-4-14ar (SWS)-4 XN) – 3 layers of glass. Inner and outer glass with selective coating, middle glass is clear glass. Warm edge is included in gaps - Swisspacer (advanced), gaps are filled with argon gas – 90%.

** Doors opens to inside;

*** Doors opens to outside;

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895



Declaration of performance

ESD/DOP-Nr.265

1. Product system	PVC Euro70 I TATRO
2. Application	Terrace doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Single sash Terrace door (76mm PVC threshold)**	Double sash Terrace door (76mm PVC threshold)**
Product ID	ETD	EDT
Product measurements	1230x2180	2000x2180
Air permeability (EN 12207)	4	4
Water tightness (EN 12208)	9A	9A
Wind resistance (EN 12210)	B5/C5	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*1,2	*1,3
Light transmission T_L , % (EN 410)	*82	*82
Solar energy transmission g , % (EN 410)	*65	*65
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	*a 44 (-1;-3) *b 45 (-1;-2)	*a 44 (-1;-3) *b 45 (-1;-2)

* formula of glass panel (4-16ar (SWS)-4 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is clear glass. Warm edge is included in gap - Swisspacer (advanced), gap is filled with argon gas – 90%;

*a formula of glass panel (44.2 SS-16ar-10 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

*b formula of glass panel (66.2 SS-16ar-8 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them.

** Opens to inside and to outside

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895



Declaration of performance

ESD/DOP-Nr.266

1. Product system	PVC Euro70 I TATRO
2. Application	Terrace doors for residential and non-residential construction
3. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus, Lithuania
4. Performance assessment system	3
5. Conformity standard:	EN 14351-1:2006 + A1:2016
6. Notified testing authority:	Institute für Fenstertechnik e.V., Rosenheim (nr 075)

This declaration of conformity is issued under the sole responsibility of the manufacturer, products in the table below are in accordance with EN 14351-1:2006 + A1:2016 standard and verified by assessment of the notified bodies.

Characteristics	Single sash Terrace door (76mm PVC threshold)**	Double sash Terrace door (76mm PVC threshold)**
Product ID	ETD	EDT
Product measurements	1230x2180	2000x2180
Air permeability (EN 12207)	4	4
Water tightness (EN 12208)	9A	9A
Wind resistance (EN 12210)	B5/C5	B2
Thermal transmittance U_w (EN ISO 10077-1 & EN ISO 10077-2), $W/m^2 K$	*0.91	*0.92
Light transmission T_L , % (EN 410)	*73	*73
Solar energy transmission g , % (EN 410)	*53	*53
Acoustic performance (EN ISO 140-1:1997+A1:2004), $R_w (C;C_{tr})$ dB	*a 44 (-1;-3) *b 45 (-1;-2)	*a 44 (-1;-3) *b 45 (-1;-2)

* formula of glass panel (4XN-14ar (SWS)-4-14ar (SWS)-4 XN) – 3 layers of glass. Inner and outer glass with selective coating, middle glass is clear glass. Warm edge is included in gaps - Swisspacer (advanced), gaps are filled with argon gas – 90%;

*a formula of glass panel (44.2 SS-16ar-10 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them;

*b formula of glass panel (66.2 SS-16ar-8 XN) – 2 layers of glass. Inner glass with selective coating, outer glass is laminated glass with sound reducing film between them.

** Opens to inside and to outside

On behalf of manufacturer signed by:

Arturas Radzevičius

Product technologist - constructor

UAB "Aradas"

LT-62175, Alytus

HEADQUARTERS

ADDRESS ŠVITRIGAILOS 11H, LT-03228, VILNIUS

EMAIL INFO@ARADAS.LT

PRODUCTION

ADDRESS GAMYBOS 12, LT- 62175, ALYTUS

PHONE +370 315 58 895